

12 Kilo Shop Roaster

US Millennium 25 pounds per batch

choose the MODEL

Features

- Auto-CAD designed quality steel body
- Stainless steel drum
- Separate chaff collector
- All precision machined parts
- Delivered ready to run
- Produces four full roasts per hour
- Heavy duty motor control center includes industrial duty components
- UL listed industrial duty electrical system
- Approved gas control
- Swing arm control panel or optional console
- Four separate US made motors for long lasting durability
- Complete with two fans to allow the professional total control over air flow and fast cooling times
- Optional standard or custom control
- Different heating methods are available
- 100% made in the USA
- Speed controlled exhaust fan and optional drum speed control
- Roasts from 4 ounces to a full load

Manually Operated

Simple operation with analog air, digital bean temperature and manual gas valve.

Standard Control System

Dual staging gas/heat control system with info sense thermocouple.

Ratio Controlled Burner

Coupled to a speed controlled fan with fingertip control.

Profiling System

Graphic touch screen roaster. The easiest and one of the most proven models on the market. From simple manual operation to automation linked to the web.

Automated Roasters

From the complete plant to just starting the cooling and opening

Specifications

Specs	12 Kilo
Weight	1000 lbs
Height to top of load hopper	5'10"
Width	32"
Depth	5'8"
BTU's	approx. 30-100,000 adjustable or 22,000-150,000 w/power burner

Cyclone is for 6" pipe for venting
Fireplace type from first perforation of ceiling to 3 foot above Roofline.
Voltages, 10 amps 208-230 or 18 amps 110-120 60 cycle. Others on request.

Specifications may change. Please contact us for current offerings.



US Roaster Corp

1530 West Main Street | Oklahoma City, OK 73106 | www.usroastercorp.com
phone 405.232.1223 | fax 405.232.1255 | info@roastersexchange.com